



# GPS Internal Active Antenna

## JCA044P



### DIMENSIONS




**SPECIFICATIONS**

Item		Specifications
Antenna	Center Frequency	1575.42 ± 1MHz
	Band Width	CF ± 5MHz
	Polarization	Linear
	Gain	1dBi (Zenith)
	V.S.W.R	<2.0
	Impedance	50 Ω
LNA	Gain	26 ± 2dB
	Noise Figure	<2.0
	Supply Voltage	2.7~3.3V DC
	Current Consumption	<14mA@3.3V
	V.S.W.R	<2.0
Mechanical	PCB Material	FR4
	Mounting Method	Soldering
Environmental	Operating Temperature	-40°C~+85°C
	Relative Humidity	Up to 95%
	Vibration	10 to 55Hz with 1.5mm amplitude 1 hours
	Environmentally Friendly	ROHS Compliant

**Radiation Pattern**


JCA044P



XY PLANE

— 1575.42MHz

JCA044P




XZ PLANE


— 1575.42MHz

JCA044P


YZ PLANE



— 1575.42MHz




**Recommended Pads**



PIN	APPLICATION
1	GND
2	GND
3	RF OUT, DC IN
4	GND
5	GND

Suggest  $X \geq 50\text{mm}$

Unit:mm





*Jinchang Electron Global Service*

**JIAXING JINCHANG ELECTRONIC TECHNOLOGY CO.,LTD**

Add: 398#, Zhenye Road, South Street, Jiaxing, Zhejiang, China

Http://www.jinchanggps.com E-mail:jcgps@vip.163.com

Tel: 86-0573-83692157/83692605/83958637 Fax:86-0573-83958635